



Recc all piping to be sized per ASHRAE F36.

Note: This drawing shows suggested piping configuration. Check with local codes and ordinances for additional requirements.

\*BALANCE VALVE "A" AND "B" TO MAINTAIN MINIMUM  F INLET TEMPERATURE BOILER MUST BE SET FOR ON/OFF FIRING MODE ONLY

<p>THIS DRAWING AND THE INFORMATION DEPICTED THEREIN IS THE PROPERTY OF CHC, CALIFORNIA HYDRONICS CORP. COPIES ARE ISSUED IN STRICT CONFIDENCE AND ARE NOT TO BE REPRODUCED OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURING, INSTALLATION OR SALE OF PRODUCT WITHOUT PRIOR WRITTEN PERMISSION OF CHC.</p>		<p>PROJECT NAME: PROJECT LOCATION: ENGINEER: CUSTOMER:</p>	
<p>PROJECT TITLE: DRAWING TITLE: HYDRONIC PRIMARY/SECONDARY - 3 SEALED COMBUSTION BOILERS WITH SEPARATE PRIMARY PUMP POWER, CIRCUIT SETTLER PROTECTION, WITH 2 SYSTEM PUMPS</p>		<p>DRAWING No. H-PS-201-3CS-2 DRAWN BY/DWG. DATE: D.K. 05/23/08 TOLERANCES UNLESS OTHERWISE SPECIFIED: 300" CHECKED/ APPROVED/ DEC. 500" ANGLE 5° SCALE NTS</p>	
<p>PROJECT NAME: PROJECT LOCATION: ENGINEER: CUSTOMER:</p>		<p>REV A SCALE NTS</p>	
<p>DESCRIPTION</p>		<p>DATE: RSG 05/28/08</p>	
<p>RELEASED</p>		<p>BY</p>	
<p>DESCRIPTION</p>		<p>DATE</p>	
<p>REV</p>		<p>DATE</p>	

